

5322 W Missouri Ave  
Glendale AZ 85301



Office (623)842-0690  
Fax (623)842-1044

## Technical Data Sheet SUNGUARD JOINT SEALANT SK300 Trowel Grade, Elastomeric Caulking (Smooth & Textured)

**Product Name:** SUN-KOTE 300 (SK300)

**Manufacturer:**

Sun Tech Coatings Mfg.  
6027 N. 57<sup>th</sup> Drive  
Glendale AZ 85301  
Phone: 623-842-0690  
Fax: 623-842-1044

**Product Description:** SUN-KOTE 300 multipurpose elastomeric sealant is an extremely tough, flexible solution for roofing and outdoor/indoor construction materials. SJS is designed for filling cracks and seams. It is a non-sag, trowel grade sealant that requires no field mixing and has excellent adhesion to all household and roofing materials without priming. It is ideal for multiple courses and encapsulant/fabric systems. Adhesion to foam, roofing and construction materials is excellent.

**Advantages:** SUN-KOTE 300 has outstanding elongation properties allowing it to contract and expand with a variety of materials, thereby maintaining a constant seal. SUN-KOTE 300 has the following advantages:

- Paintable
- Weatherproof
- Exceptional elongated and flexibility
- Outstanding adhesion to all building surfaces
- Flexible in hot & cold temperatures
- Easy water clean-up
- Fast drying

**Coverage:** Most applications, apply 40 square feet per gallon or 25 linear feet per cartridge for a 1/4" x 1/4" joint. Actual coverage will vary considerably depending upon condition of the roof surface.

**Basic Application:**

- Stucco
- New Work
- Masonry
- Concrete
- Brick
- Wood Hardwood
- Drywall
- EPS board
- Roof Systems

**Colors:** SUN-KOTE 300 is white in color. Custom colors are available. (11 tube Minimum.)

**Painting:** SUN-KOTE 300 is tack free in 1 hour at 75°F and may be painted in 24 hours with latex or oil based paints.

**Surface Preparations:** All surfaces should be clean, dry, and free from dirt, dust, grease, loose peeling paint and all other foreign matter.

**Packaging:**

- SK063-14 – 10.6 Fl Oz Cartridge
- SK063-01- 1 Gallon Plastic Pail
- SK063-05- 5 Gallon Plastic Pail

**Net Weight:**

- SK063-14 – 14 Ounces
- SK063-01- 12 Pounds
- SK063-05- 58 Pounds

**Drying Time :**

- To Touch – 1 hour
- To Re-Coat – Overnight

**Clean Up:** Clean tools with water. Do not allow spills to dry. Clean up immediately with warm soapy water.

**Basic Uses:**

- Patching and sealing hairline cracks
- Concentrating scars caused by heavy paint peeling.
- Seals joints and cracks on roofs

- Filling wide cracks and expansion joints
- Sealing plumbing or electrical intakes.
- Bedding for various types of flashing

**Application:** Apply with a putty knife or paint brush level or remove excess sealant with a wet tooling stick or knife.

**Properties:**

- Solids (Weight) – 78.0 +/-5%
- Solids (Volume) – 63.0 +/-5%
- pH – 8.5 – 9.5
- V.O.C – Less than 250 grams Per Liter

**Precautions:** Do not take internally. If swallowed do not induce vomiting. Seek medical attention immediately. If contact with eyes occurs flush thoroughly with water and seek medical attention immediately. Avoid prolonged or repeated contact with skin. May cause skin irritation or sensitivity. Wear glasses and eye protection.

**Do Not Freeze:** Store between 50°F and 90°F. Solidification and destruction of this product will be the result of freezing.

**Important:** Apply a sample to a small inconspicuous area to ensure application meets your expectations.

**SEE** MSDS for more information.

[www.suntechcoatings.com](http://www.suntechcoatings.com)

